

# CLOVER



All-in-one POS terminal

## CLOVER 8700 シリーズ

15 インチ True Flat タッチパネルを採用。

置き場所も選ばないファンレス静音設計。

オプションで背面ディスプレイ (10.1 インチ) も搭載可能、

コスト重視・パフォーマンス重視の 2 種類をラインナップ。

厳しい環境下でも対応可能なフルメタル設計 (モニター筐体・スタンド)



Specification	CLOVER 8750	CLOVER 8760	CLOVER 8770	CLOVER 8780
<b>Motherboard</b>				
Processor	Intel® Celeron® Processor N3060	Intel® Celeron® Processor N3160	Intel® Core™ Processor i5-6500TE	Intel® Celeron® Processor N3160
System Memory	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)	4GB, 1 x DDR4 (exp. up to 16GB) - 2133MHz (1.2V)	4GB, 1 x DDR3L (exp. up to 8GB) - 1600MHz (1.35V)
<b>LCD Touch Panel</b>				
LCD Size	15" LED LCD	18.5" LED LCD	18.5" LED LCD	15" LED LCD
Brightness	300 cd/m <sup>2</sup>			
Resolution	1024 x 768	1366 x 768	1920 x 1080	1024 x 768
Touch Screen	True Flat Resistive	Projected Capacitive with 10 touch points		
Tilt Adjustment	TBS			
<b>Storage Device</b>				
Hard Drive	64 GB SSD, expandable	64 GB SSD, expandable	256 GB SSD, expandable	64 GB SSD, expandable
<b>Expansion</b>				
Mini PCI-E Socket	1			
<b>External I/O Ports</b>				
USB Port	4 x USB (2 x USB 3.0, 2 x USB 2.0)	6 x USB (2 x USB 3.0, 4 x USB 2.0)	6 x USB (2 x USB 3.0, 4 x USB 2.0)	4 x USB (2 x USB 3.0, 2 x USB 2.0)
Serial Port	4 x COM ports RJ-45 connectors (2 ports with power: 5V=green LED/12V=yellow LED, enabled by BOIS)			
Parallel Port	N/A			
LAN Port	1 x RJ-45 (10/100/1000Mbps Giga LAN)			
Second Display	1x HDMI (12V power by DC-jack, enabled in BIOS)			
Cash Drawer Port	1 x RJ-11 (12V/24V)			
DC Jack	1			
Audio Jack	1 x combo: mic & line out			
<b>Audio</b>				
Internal Speaker	1 x 2W	2 x 2W		1 x 2W
<b>Power</b>				
Power Supply	Adapter (DC 65W,19V,3.42A)	Adapter (DC 90W,19V,4.74A)	Adapter (DC 120W,19V,6.32A)	Adapter (DC 65W,19V,3.42A)
<b>Control / Indicator</b>				
Power Button	1			
<b>Peripheral</b>				
MSR	3 Tracks MSR USB (option)			
Finger print	1 (USB) (option)			
iButton	Option			
Second Display	2x20 VFD or 10.1" , 14" or 15" Second LCD Display with or without touch (option)			
<b>Certificate</b>				
EMC & Safety	FCC, CE			
<b>Environment</b>				
Operating Temperature	0°C to +60°C (+32°F to +140°F)			
Storage Temperature	-20°C to +80°C (-4°F to +176°F)			
Operating Humidity	10% to 90% RH non-condensing			
Storage Humidity	10% to 90% RH non-condensing			
<b>Dimension (W x D x H)</b>	360 x 200 x 340 mm	470 x 200 x 350 mm	470 x 200 x 350 mm	360 x 200 x 340 mm
<b>Weight</b>	5.6 kg	6.9 kg	6.9 kg	5.6 kg
<b>Mounting</b>	70mm x 70mm & 100mm x 100mm VESA mounting hole for panel PC type			
<b>OS Installed</b>	Windows® 10 Enterprise 2016 LTSB			
<b>OS Supported</b>	Linux, Windows® 8, Windows® 8.1, Windows® 10			



10.1インチのリアモニター(オプション)



高さ約 34cm、奥行き約 21cm



最大約 60度

**CLOVER**

クローバー電子 株式会社  
〒519-0501 三重県伊勢市小俣町明野 306-1  
TEL : 0596-37-5151(代) FAX : 0596-37-0808